## Balemaster's Automatic Continuous Open-End Baler

The High Density E-Series





Balemaster Baler with Automatic Wire tying, MODEL E-430

## **Labor and Money Saving Features:**

NO BALER OPERATOR: Heavy-duty automatic wire tying for maximum automation and rapid return on investment. Tier supplied initially or added at a future date.

## PRODUCTION AND PERFORMANCE:

Models to meet your requirement from 5 bales per day to 10 bales per hour. Bale density, depending on material ranging from 25-30 lbs. per cubic foot.

FREIGHT SAVINGS: Models available with main baling cylinder diameters to meet bale density requirements. Optimum bale density comes by using hydraulic Side Cylinder Density Control with completely automatic adjustment on each stroke of the baling ram.

**PAPER DUST CONTROL:** Accomplished with our "Designed-in" encapsulated baling ram compartment which provides decreased dust – and fire hazard – in the general baling area resulting in better employee safety and morale.

RELIABILITY WITH REDUCED
OPERATING COST: Simplicity of design
provides the ultimate machine
sophistication. Readily accessible hydraulic
components with Energy Efficient Hydraulic
Power Package reduce operation costs and
provide extra capacity.

**DEPENDABILITY:** Heavy welded structure with the finest hydraulic and electrical components. All necessary electrics and controls supplied.





Balemaster

