

ECOTAINER Balers & Containers Western Canada Sales & Service Toll Free: 1-800-561-6525

www.ecotainer.ca

AMS-500HD / AMS-750HD / AMS-1000HD HARD DRIVE SHREDDERS Durable, Reliable & Mobile

Options:

- Air particulate system: (See 2nd page)
- Powder coat color
- Backlit laser burned logos
- Mobile truck installation

Requirements:

- 230v single phase power reduces throughput by approximately 10%
- 3/4" and 1" shred widths are only available on AMS-750HD


SPECIFICATION CHART			
Motor	5, 7.5 OR 10 HP TEFC		
Shred Width	1-1/2", 1" or 3/4"		
Infeed	11" W x 2.5" H		
Voltage	208/230/460v 1 or 3 Phase		
Output	Discharge Conveyor		
Dimensions	77" L x 56" W x 56" H		



Model Number	Shred Width	Horse Power	Standard Drives / Hour	Server Drives / Hour	Weight
AMS-1000HD	1-1/2"	10 HP	2000	1000	3400 Lbs.
AMS-750HD	1-1/2"	7.5 HP	1800	900	2700 Lbs.
AMS-500HD	1-1/2"	5 HP	1500	750	2500 Lbs.
AMS-1000HD	1"	10 HP	1500	750	3500 Lbs.
AMS-750HD	1"	7.5 HP	1350	675	2800 Lbs.
AMS-1000HD	3/4"	10 HP	1000	500	3600 Lbs.
AMS-750HD	3/4"	7.5 HP	900	450	2900 Lbs.

AMS-1000HD is not available in single phase power

SPECIFICATIONS





ECOTAINER Balers & Containers Western Canada Sales & Service Toll Free: 1-800-561-6525

www.ecotainer.ca

AIR FILTRATION SYSTEMS Optional on Hard Drive Shredders Series 2 & Series 3

The AMS air filtration system was designed to help reduce possible odors and/or contaminants from escaping into the atmosphere during hard drive destruction.

Standard Features:

- Inexpensive and disposable pre-filter protects the blower and HEPA filter
- The blower is housed in cast aluminum
- The blast gate serves as an air flow control valve

SPECIFICATION CHART				
Motor	1 HP TEFC			
Air Flow	400 CFM at 3" static water gauge pressure			
Efficiency	99.97% on particles 0.3 micron and larger			



Ameri-Shred's air filtration systems consist of six major components which include the inlet, pre-filter, blower, blast gate, HEPA filter and ductwork.

An air filtration system must be part of your original order. It cannot be retrofit at a later date.